

# ASPUN™ 6835A

Fiber Grade Resin  
The Dow Chemical Company

## Message:

Designed for processing into yarn and bonding fibers  
Complies with U.S. FDA 21 CFR 177.1520 (c) 3.2a.  
Consult the regulations for complete details.  
ASPUN™ 6835A Fiber Grade Resin is a linear low density polyethylene (LLDPE). A typical process is staple fiber production.

General Information			
Agency Ratings	FDA 21 CFR 177.1520(c) 3.2a		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.950	g/cm <sup>3</sup>	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	17	g/10 min	ASTM D1238
Thermal	Nominal Value	Unit	Test Method
Melting Temperature (DSC)	129	°C	Internal method
Additional Information			

建议的最佳工艺:可梳理切段纤维典型应用:纱线和粘合纤维

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
Phone: +86 13424755533  
Email: sales@su-jiao.com  
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

