

# Vinnolit® E 67 ST

Polyvinyl Chloride Homopolymer

Vinnolit GmbH & Co. KG

### Message:

Vinnolit E 67 ST is a very fine-particle, paste-making emulsion homopolymer, giving medium viscosity plastisols with a good shelf life. Plastisols made with Vinnolit E 67 ST have a slightly pseudoplastic rheology.  
Vinnolit E 67 ST exhibits excellent foaming characteristics in chemically blown foams, particularly for screen printing and hot embossing for wall covering manufacturing.

General Information			
Uses	Foam		
Agency Ratings	EC 1907/2006 (REACH)		
Processing Method	Plastisol		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.39	g/cm <sup>3</sup>	ISO 60
K-Value	67.0		ISO 1628-2
Viscosity Number (Reduced Viscosity)	112.0	ml/g	ISO 1628
Emulsifier Content	Medium		
Particle Size Distribution <sup>1</sup>	< 0.35	%	ISO 4610
Volatile Matter	< 0.50	%	ISO 1269
NOTE			

1. retained on 0.063 mm screen

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
Phone: +86 13424755533  
Email: sales@su-jiao.com  
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

