# Sinvicomp SBF5758

### Rigid Polyvinyl Chloride

Teknor Apex Asia Pacific PTE. LTD.

#### Message:

Sinvicomp SBF5758 is a Rigid Polyvinyl Chloride material. It is available in Asia Pacific for blow molding. Primary attribute of Sinvicomp SBF5758: Food Contact Acceptable.

Typical application of Sinvicomp SBF5758: Wrap

General Information			
Features	Food Contact Acceptable		
Uses	Shrink Wrap		
Forms	Pellets		
Processing Method	Blow Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.32	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/21.6			
kg)	54	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	39.2	MPa	ASTM D638
Tensile Elongation (Break)	190	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	98	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	77.0	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

