

Fainplast PVC CTS 01426/2

Polyvinyl Chloride Alloy

Fainplast Compounds S.r.l

Message:

Fainplast PVC CTS 01426/2 is a Polyvinyl Chloride Alloy (PVC Alloy) product. It can be processed by extrusion and is available in Africa & Middle East, Europe, Latin America, or North America. Typical application: Engineering/Industrial Parts.

| General Information | | | |
|-------------------------------|---------------|-------------------|-------------|
| Uses | Gaskets | | |
| Processing Method | Extrusion | | |
| Physical | Nominal Value | Unit | Test Method |
| Density | 1.27 | g/cm ³ | ISO 1183 |
| Hardness | Nominal Value | Unit | Test Method |
| Shore Hardness (Shore A) | 73 | | ISO 868 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Stress (Break) | > 16.5 | MPa | ISO 527-2 |
| Tensile Strain (Break) | > 550 | % | ISO 527-2 |
| Elastomers | Nominal Value | Unit | Test Method |
| Tear Strength | 8.00 | kN/m | |
| Compression Set (23°C, 22 hr) | < 35 | % | |
| Thermal | Nominal Value | Unit | |
| Thermal Stability | 50 | min | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

