Selar® PA 3426R

Polyamide 6I/6T Copolymer

DuPont Packaging & Industrial Polymers

Message:

Selar® PA 3426R is an amorphous nylon (polyamide) resin which exhibits superior transparency, good barrier properties to gases, water, solvents and essential oils and high temperature structural properties which make it suitable for consideration in a number of applications. It is available in the form of small, free flowing pellets in 25 kg (55 lb.) foil-lined bags or 750 kg. (1653 lb.) foil lined boxes.

General Information						
Features	Amorphous					
	Barrier Resin					
	Food Contact Acceptable					
	High Clarity					
	High Gloss High Stiffness High Viscosity					
				Solvent Resistant		
	Uses	Bottles				
Film						
Packaging						
Tubing						
Vials						
Agency Ratings	FDA 21 CFR 177.1500(a)(12)					
Appearance	Clear/Transparent					
Forms	Pellets					
Processing Method	Blow Molding					
	Coextrusion					
	Extrusion					
	Injection Molding					
Physical	Nominal Value	Unit	Test Method			
Specific Gravity	1.19	g/cm³	ASTM D792, ISO 1183			
Intrinsic Viscosity	0.82		ASTM D5225			
Moisture When Packaged	< 0.10	%	ISO 15512			
Thermal	Nominal Value	Unit	Test Method			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

125

Glass Transition Temperature

°C

DSC

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

