

ELASTEL™ AF-1

Ethylene Vinyl Acetate Copolymer
HELLENIC CABLES S.A.

Message:

Description: EVA based compounds for sheaths in elastic power cables
Specifications:
i) VDE 207 TEIL 24 TYPE HM1
ii) BS 6833 TYPE RS3-C
Packaging: In carton boxes of approximately 400-1000 kg
Types of cables where it can be used: EPR/EVA TYPE D2&E2, EPR/EVA/CWB/EVA, EPR/ZHLS, etc.

General Information		
Uses	Wire & Cable Applications	
RoHS Compliance	RoHS Compliant	
Processing Method	Extrusion	
Physical	Nominal Value	Unit
Specific Gravity	1.56	g/cm³
Extrusion	Nominal Value	Unit
Cylinder Zone 1 Temp.	55.0	°C
Cylinder Zone 2 Temp.	60.0	°C
Cylinder Zone 3 Temp.	60.0	°C
Head Temperature	60	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT