

Caltex PP MC41

Polypropylene

GS Caltex

Message:

Caltex PP MC41 is a Polypropylene material. It is available in Asia Pacific.

Important attributes of Caltex PP MC41 are:

Flame Retardant

Heat Resistant

High Gloss

High Stiffness

Typical application of Caltex PP MC41: Electrical/Electronic Applications

General Information			
Features	Flame Retardant		
	High Gloss		
	High Heat Resistance		
	High Stiffness		
Uses	Electrical Parts		
	Electrical/Electronic Applications		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.970	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR)	8.5	g/10 min	ASTM D1238
Molding Shrinkage			ASTM D955
Flow	1.6	%	
Across Flow	1.5	%	
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	83		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	26.5	MPa	ASTM D638
Tensile Elongation (Break)	160	%	ASTM D638
Flexural Modulus	1320	MPa	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	74	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	100	°C	ASTM D648
Vicat Softening Temperature	148	°C	ASTM D1525
Injection	Nominal Value	Unit	
Processing (Melt) Temp	210 to 230	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

