# Hifax CB 237 G 1312

### Polypropylene Copolymer

#### LyondellBasell Industries

#### Message:

Hifax CB 237 G is a 15% talc filled elastomer modified PP, with good flowability, excellent impact/stiffness balance and good UV resistance. This product is also available in other colors, new colors can be developed depending on customer requirements. For regulatory compliance information, see Hifax CB 237 G 1312 Product Stewardship Bulletin (PSB) and Safety Data Sheet (SDS). This grade is not intended for medical, pharmaceutical, food and drinking water applications.

General Information					
Filler / Reinforcement	Mineral filler, 15% filler by weight				
Additive	Impact modifier				
	UV stabilizer				
Features	Impact modification				
	Rigid, good				
	Copolymer				
	Impact resistance, good				
	Good UV resistance				
	Good liquidity				
	Good color stability				
	Good wear resistance				
	Non-toxic				
	Excellent appearance				
Uses	Application in Automobile Field				
	Automotive exterior parts				
	Car exterior decoration				
Forms	Particle				
Physical	Nominal Value	Unit	Test Method		
Density	1.01	g/cm³	ISO 1183/A		
Melt Mass-Flow Rate (MFR) (230°C/2.16			100 1100		
kg)	14	g/10 min	ISO 1133		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Stress (Yield, 23°C) Flexural Modulus <sup>1</sup> (23°C)	18.0	MPa	ISO 527-2		
	1700	MPa	ISO 178/A		
Impact	Nominal Value	Unit	Test Method		
Charpy Notched Impact Strength	7.0	1.1/2	ISO 179/1eA		
0°C	7.0	kJ/m <sup>2</sup>	ISO 179/1eA		
23°C	20	kJ/m²	ISO 179/1eA		

Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (0.45 MPa, Unannealed)	90.0	°C	ISO 75-2/B
NOTE			
1.	1.0 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

