# Yuyao PA 05ZR16

### Polyamide 66/6 Copolymer

Yuyao Tenglong Plastics Co., Ltd.

#### Message:

Yuyao PA 05ZR16 is a Polyamide 66/6 Copolymer (Nylon 66/6) product. It can be processed by injection molding and is available in Asia Pacific. Applications of Yuyao PA 05ZR16 include electrical/electronic applications, appliances, automotive, furniture and industrial applications. Characteristics include: Impact Resistant Impact Modified

General Information Additive Impact Modifier Features High Impact Resistance Impact Modified Low Temperature Impact Resistance Uses Appliance Components Automotive Applications **Camera Applications** Furniture Industrial Applications Power/Other Tools Sporting Goods Switches **Processing Method** Injection Molding Physical Nominal Value Unit Test Method Specific Gravity 1.08 g/cm<sup>3</sup> ASTM D792 Molding Shrinkage - Flow 15 % ASTM D955

Molding Shrinkage - Flow	1.5	%	ASTM D955
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	58.0	MPa	ASTM D638
Tensile Elongation (Break)	130	%	ASTM D638
Flexural Modulus	1100	MPa	ASTM D790
Flexural Strength	70.0	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (Area)	25.0	kJ/m²	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8	}		
MPa, Unannealed)	70.0	°C	ASTM D648
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity	1.0E+15	ohms•cm	ASTM D257
Injection	Nominal Value	Unit	

Drying Temperature	85.0 to 90.0	°C
Drying Time	6.0 to 8.0	hr
Processing (Melt) Temp	235 to 265	°C
Mold Temperature	60.0 to 90.0	°C
Injection Pressure	60.0 to 100	МРа

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

