

Karina PVC COMPOUND COLOR WHITE - E-818-10/23-CRM-AS

Polyvinyl Chloride
Karina Ind. e Com. de Plásticos Ltda

Message:
U.V. PROTECTION ADDED.

General Information			
Additive	UV Stabilizer		
Features	Good UV Resistance		
Appearance	White		
Physical	Nominal Value	Unit	Test Method
Specific Gravity ¹	1.33 to 1.39	g/cm³	ASTM D792
Color a	-1.42 to 0.180		ME 12
Color b	1.05 to 2.65		ME 12
Color L	92.6 to 94.2		ME 12
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D, 15 sec)	78 to 82		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	> 34.3	MPa	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	> 72.0	°C	ASTM D1525
NOTE			
1.	24 hr		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT