Hostacom XBR 169 G C12463

Polypropylene Copolymer LyondellBasell Industries

Message:

Hostacom XBR 169 G C12463 is a 15% talc filled PP copolymer, with excellent impact/stiffness balance, good scratch resistance and good surface appearance. Significant reduction of mineral filler contributes to the reduction of final part weight. It has been designed using the latest advancements in resin synthesis and compounding technology. Product is available as a customized color matched, pellet form. This grade is delivered in C12463 color version.

This grade is not intended for medical, pharmaceutical, food and drinking water applications.

Features Rigid, good Copolymer Impact resi Scratch res Good appe Uses Application Car interior	istance, good sistance earance n in Automobile Field r equipment	
Copolymer Impact resi Scratch res Good appe Uses Application Car interior Appearance Available c Forms Particle Processing Method Injection m Physical Nominal Val Density (23°C) 1.02 Melt Mass-Flow Rate (MFR) (230°C/2.16	istance, good sistance earance n in Automobile Field r equipment	
Impact resi Scratch res Good appe Uses Application Car interior Appearance Available of Forms Particle Processing Method Injection management Physical Nominal Val Density (23°C) 1.02 Melt Mass-Flow Rate (MFR) (230°C/2.16	istance, good sistance earance n in Automobile Field r equipment	
Uses Application Car interior Appearance Forms Particle Processing Method Injection m Physical Nominal Val Density (23°C) Melt Mass-Flow Rate (MFR) (230°C/2.16	earance n in Automobile Field r equipment	
Uses Application Car interior Appearance Available of Forms Particle Processing Method Injection model Physical Density (23°C) Melt Mass-Flow Rate (MFR) (230°C/2.16	earance n in Automobile Field r equipment	
Uses Application Car interior Appearance Available of Forms Particle Processing Method Injection model Physical Nominal Value Density (23°C) 1.02 Melt Mass-Flow Rate (MFR) (230°C/2.16	n in Automobile Field r equipment	
Appearance Available c Forms Particle Processing Method Injection m Physical Nominal Value Density (23°C) 1.02 Melt Mass-Flow Rate (MFR) (230°C/2.16	r equipment	
Appearance Available c Forms Particle Processing Method Injection m Physical Nominal Value Density (23°C) 1.02 Melt Mass-Flow Rate (MFR) (230°C/2.16	r equipment	
Appearance Available of Forms Particle Processing Method Injection management Physical Nominal Value Density (23°C) 1.02 Melt Mass-Flow Rate (MFR) (230°C/2.16		
Forms Particle Processing Method Injection m Physical Nominal Val Density (23°C) 1.02 Melt Mass-Flow Rate (MFR) (230°C/2.16	olors	
Forms Particle Processing Method Injection m Physical Nominal Val Density (23°C) 1.02 Melt Mass-Flow Rate (MFR) (230°C/2.16	olors	
Processing Method Injection m Physical Nominal Val Density (23°C) 1.02 Melt Mass-Flow Rate (MFR) (230°C/2.16		
Physical Nominal Val Density (23°C) 1.02 Melt Mass-Flow Rate (MFR) (230°C/2.16	Particle	
Density (23°C) 1.02 Melt Mass-Flow Rate (MFR) (230°C/2.16	nolding	
Melt Mass-Flow Rate (MFR) (230°C/2.16	ue Unit	Test Method
	g/cm³	ISO 1183/A
kg) 18		
3,	g/10 min	ISO 1133
Mechanical Nominal Val		Test Method
Tensile Stress (Yield, 23°C) 18.5	MPa	ISO 527-2
Flexural Modulus ¹ (23°C) 1650	MPa	ISO 178/A
Impact Nominal Val	ue Unit	Test Method
Charpy Notched Impact Strength		ISO 179/1eA
-40°C 2.5	kJ/m²	ISO 179/1eA
23°C 40	kJ/m²	ISO 179/1eA
Notched Izod Impact		ISO 180/1A
-40°C 3.0	kJ/m²	ISO 180/1A
23°C 35	kJ/m²	ISO 180/1A
Thermal Nominal Val	ue Unit	Test Method
Heat Deflection Temperature (0.45 MPa, Unannealed) 95.0	°C	ISO 75-2/B

1. 1.0 mm/min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

