

Yuyao PPO GFN3-801

Polyphenylene Ether + PS
Yuyao Tenglong Plastics Co., Ltd.

Message:

Yuyao PPO GFN3-801 is a Polyphenylene Ether + PS (PPE+PS) product filled with glass fiber. It can be processed by injection molding and is available in Asia Pacific. Typical application: Engineering/Industrial Parts.
Characteristics include:
Flame Rated
Eco-Friendly/Green
Good Dimensional Stability
Halogen Free
Heat Resistant

General Information			
Filler / Reinforcement	Glass Fiber		
Features	Environmentally Sound		
	Good Dimensional Stability		
	Halogen Free		
	High Heat Resistance		
	High Strength		
	Hydrolysis Resistant		
Uses	Pump Parts		
	Valves/Valve Parts		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.30	g/cm ³	ASTM D792
Molding Shrinkage - Flow	0.30 to 0.50	%	ASTM D955
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	100	MPa	ASTM D638
Tensile Elongation (Break)	3.0	%	ASTM D638
Flexural Modulus	7200	MPa	ASTM D790
Flexural Strength	160	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (Area)	10.0	kJ/m ²	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	130	°C	ASTM D648
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity	2.3E+3	ohms · cm	ASTM D257
Flammability	Nominal Value	Unit	Test Method
Flame Rating	UL 94		

1.60 mm	HB
3.20 mm	HB

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

