

Evermore PUR SS-143G

Polyurethane

Evermore Chemical Industry Co., Ltd.

Message:

Evermore PUR SS-143G is a Polyurethane product. It is available in Asia Pacific. Typical application: Fabrics/Fibers.

Characteristics include:

Antiblock

High Gloss

High Hardness

General Information	
Additive	Antiblock
Features	Aliphatic
	Antiblocking
	High Gloss
	High Hardness
Uses	Synthetic Leather
	Textile Applications

Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	10.8 to 14.7	MPa	ASTM D412
Tensile Strength (Yield)	44.1 to 63.7	MPa	ASTM D412
Tensile Elongation (Break)	300 to 500	%	ASTM D412
Fill Analysis	Nominal Value	Unit	Test Method
Melt Viscosity (25.0°C)	50.0 to 90.0	Pa·s	ASTM D3835
Additional Information	Nominal Value	Unit	Test Method
Non-Volatile Content	29 to 31	%	
Solvents	DMF, MEK		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT