

Taipol 4202

Styrene Butadiene Styrene Block Copolymer

TSRC Corporation

Message:

Taipol 4202 is a Styrene Butadiene Styrene Block Copolymer (SBS) product. It is available in Asia Pacific. Applications of Taipol 4202 include additive/masterbatch, adhesives/tapes and consumer goods.

Characteristics include:

- Clarity
- High Strength
- Low Temperature Resistant
- Stabilized

General Information	
Additive	Unspecified Stabilizer 2
Features	High Clarity
	High Strength
	Low Temperature Resistant
Uses	Adhesives
	Asphalt Modification
	Footwear
	Plastics Modification

Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.958	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/5.0 kg)	3.0 to 11	g/10 min	ASTM D1238
Bound Styrene	38.5 to 41.5	%	Internal Method
Ash Content	< 0.20	%	ASTM D5667
Gel Content	< 0.10	%	Internal Method
Volatiles	< 0.50	%	Internal Method
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	92		ASTM D2240
Optical	Nominal Value	Unit	Test Method
Yellowness Index	< 4.0	YI	Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

