Generic Silicone Rubber, RTV-1

Silicone Rubber, RTV-1

Generic

Message:

This data represents typical values that have been calculated from all products classified as: Generic Silicone Rubber, RTV-1 This information is provided for comparative purposes only.

General Information			
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.988 to 1.08	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (23°C)	25 to 36		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (23°C)	0.345 to 3.00	MPa	ASTM D412
Thermal	Nominal Value	Unit	Test Method
Thermal Conductivity (23°C)	0.20 to 0.24	W/m/K	ASTM C177
Electrical	Nominal Value	Unit	Test Method
Dielectric Strength (23°C)	5.0 to 25	kV/mm	ASTM D149
Dissipation Factor (23°C)	1.0E-4 to 0.010		ASTM D150
Uncured Properties	Nominal Value	Unit	
Viscosity (23°C)	0.060 to 2.6	Pa·s	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

