

EMVIN 733

Flexible Polyvinyl Chloride

Intergulf Empol

Message:

EMVIN 733 is a Flexible Polyvinyl Chloride product. It is available in Africa & Middle East. Typical application: Wire & Cable.

Characteristics include:

Good Aesthetics

High Gloss

General Information		
Features	Good Surface Finish	
	High Gloss	
Uses	Wire & Cable Applications	
Agency Ratings	BS 7655 4.2	
Appearance	Natural Color	
Forms	Granules	
Physical	Nominal Value	Unit
Specific Gravity	1.46 to 1.50	g/cm ³
Hardness	Nominal Value	Unit
Shore Hardness (Shore A)	88	
Mechanical	Nominal Value	Unit
Tensile Stress (Yield)	> 10.0	MPa
Tensile Strain (Break)	> 180	%
Thermal	Nominal Value	Unit
Continuous Use Temperature	70.0	°C
Electrical	Nominal Value	Unit
Insulation Resistance (20°C)	> 0.300	Mohms/km
Loss of Mass - 7 days (80°C)	< 1.50	mg/cm ²
Resistance to Cracking - 1 hour (150°C)	No Cracks	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT