Ravaflex IIR

Butyl Rubber

Ravago Group

Message:

Reprocessed copolymer of isobutylene and isoprene with a very good processibility.

General Information			
Features	Copolymer		
	Antioxidation		
	Workability, good		
Appearance	White		
	Amber		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.920	g/cm³	ASTM D297
Mooney Viscosity (ML 1+8, 100°C)	45 - 75	MU	ASTM D1646
Antioxidant Additive	Nonstaining		
Moisture Content (105°C)		%	Internal method
Ash content-1 hr (550°C)		%	ASTM D297
Packaging	1000	g	
Additional Information	Nominal Value	Unit	

It shows a good resistance to oxidative and ozone degradation and has a low gas permeability.

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

