Durez® 4581

Phenolic

Sumitomo Bakelite North America, Inc.

Message:

Durez 4581 is a one-step thermosetting phenolic resin powder.

| General Information | | | |
|---------------------------------|---------------|------|-----------------|
| Forms | Powder | | |
| Physical | Nominal Value | Unit | Test Method |
| Moisture Content - Karl Fischer | 2.0 | % | Internal Method |
| Inclined Plate Flow (125°C) | 3.00 | cm | Internal Method |
| Screen Mesh ¹ | 5.0 | % | Internal Method |
| Slurry Test | No Grit | | Internal Method |
| Thermoset | Nominal Value | Unit | Test Method |
| Post Cure Time (150°C) | 0.015 | hr | |
| NOTE | | | |
| 1. | 200 Mesh | | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

