

# Shandong PP GFPP40-2

Polypropylene

Shandong Dongchen Engineering Plastics Co., Ltd.

Message:

Shandong PP GFPP40-2 is a Polypropylene material filled with glass fiber. It is available in Asia Pacific.

Important attributes of Shandong PP GFPP40-2 are:

Heat Resistant

High Strength

Rigid

Typical applications include:

Appliances

Electrical/Electronic Applications

Fabrics/Fibers

General Information	
Filler / Reinforcement	Glass Fiber
Features	High Heat Resistance
	High Rigidity
	High Strength
Uses	Appliance Components
	Electrical/Electronic Applications
	Textile Applications

Mechanical	Nominal Value	Unit
Tensile Stress (Yield)	> 60.0	MPa
Flexural Stress	> 40.0	MPa
Impact	Nominal Value	Unit
Notched Izod Impact Strength	> 8.0	kJ/m <sup>2</sup>
Unnotched Izod Impact Strength	> 40	kJ/m <sup>2</sup>
Thermal	Nominal Value	Unit
Heat Deflection Temperature (0.45 MPa, Unannealed)	> 155	°C
Additional Information	Nominal Value	Unit
Residue of Combustion	38 to 42	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: [sales@su-jiao.com](mailto:sales@su-jiao.com)

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

