Yanshan PE LD100

Low Density Polyethylene

SINOPEC Beijing Yanshan Petrochemical

Message:

Yanshan PE LD100 is a Low Density Polyethylene product. It can be processed by blow molding, cast film, film extrusion, or injection molding and is available in Asia Pacific. Applications of Yanshan PE LD100 include film, additive/masterbatch, bags/liners, coating applications and hose/tubing.

| General Information | | | |
|---------------------|-------------------|-------|-------------|
| Uses | Bags | | |
| | Blending | | |
| | Cable Jacketing | | |
| | Cast Film | | |
| | Film | | |
| | Laminates | | |
| | Packaging | | |
| | Piping | | |
| | Tubing | | |
| | | | |
| Processing Method | Blow Molding | | |
| | Cast Film | | |
| | Film Extrusion | | |
| | Injection Molding | | |
| | | | |
| Physical | Nominal Value | Unit | Test Method |
| Density | 0.923 | g/cm³ | ASTM D1505 |
| | | | |

| Physical | Nominal Value | Unit | lest Method |
|----------------------------|---------------|----------|-------------|
| Density | 0.923 | g/cm³ | ASTM D1505 |
| Melt Mass-Flow Rate (MFR) | 2.0 | g/10 min | ASTM D1238 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Strength (Yield) | 9.00 | МРа | ASTM D638 |
| Tensile Elongation (Break) | 500 | % | ASTM D638 |
| | | | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

