

TAISOX 9000

High Density Polyethylene
Formosa Plastics Corporation

Message:

TAISOX 9000 is a high density polyethylene material. This product is available in North America, Europe or Asia Pacific.
The main features of TAISOX 9000 are:
high strength
Good toughness
Typical application areas include:
bag/lining
Movie

General Information			
Features	Ultra high toughness		
	High density		
	High strength		
Uses	Films		
	Bags		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Density	0.950	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.070	g/10 min	ASTM D1238
Environmental Stress-Cracking Resistance	500	hr	ASTM D1693
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	65		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Yield	25.5	MPa	ASTM D638
Fracture	36.3	MPa	ASTM D638
Tensile Elongation (Break)	850	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Tensile Impact Strength	637	kJ/m ²	ASTM D1822
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-70.0	°C	ASTM D746
Vicat Softening Temperature	123	°C	ASTM D1525
Melting Temperature	130	°C	
Additional Information			
Notched Izod Impact Strength, ASTM D256: 22 kg-cm/cm ² Blow Up Ratio: 3 to 6			
Injection	Nominal Value	Unit	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT