

Stylac™ T8701

Acrylonitrile Styrene Copolymer
Asahi Kasei Chemicals Corporation

Message:

Stylac™ T8701 is an Acrylonitrile Styrene Copolymer (AS) product. It is available in Africa & Middle East, Asia Pacific, or Europe.

General Information			
Features	General Purpose		
	Good Flow		
Uses	General Purpose		
Physical	Nominal Value	Unit	Test Method
Density (23°C)	1.07	g/cm³	ISO 1183
Melt Mass-Flow Rate (MFR) (220°C/10.0 kg)	23	g/10 min	ISO 1133
Melt Volume-Flow Rate (MVR) (220°C/10.0 kg)	24.6	cm³/10min	ISO 1133
Molding Shrinkage - Flow	0.40 to 0.60	%	ASTM D955
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	67.9	MPa	ISO 527-2/5
Flexural Modulus ¹	3650	MPa	ISO 178
Flexural Stress ²	125	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C)	1.3	kJ/m²	ISO 179
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (1.8 MPa, Unannealed)	86.7	°C	ISO 75-2/A
Vicat Softening Temperature	102	°C	ISO 306/B
NOTE			
1.	2.0 mm/min		
2.	2.0 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT