NEFTEKHIM PP 9341S

Polypropylene Copolymer

Nizhnekamskneftekhim Inc.

Message:

Product obtained by copolymerization of propylene and ethylene in presence of complex metalorganic catalysts.

It incorporates increased long-term thermal stability, thermal-oxidative degradation resistance when PP is produced, processed and PP-made articles are exploited, antistatic properties to produce articles, effective nucleation.

Application: toys, household goods, covers, containers, jet molding.

Technical requirements: TU 2211-136-05766801-2006

General Information					
Additive	Antistatic				
	Nucleating Agent				
Features	Antistatic				
	Block Copolymer				
	Good Thermal Stability				
	Nucleated				
	Oxidation Resistant				
Uses	Containers				
	Household Goods				
	Protective Coverings				
	Toys				
Forms	Pellets				
Processing Method	Injection Molding				
Physical	Nominal Value	Unit	Test Method		
Density	0.900	g/cm³			
Apparent Density	0.48 to 0.60	g/cm³			
Melt Mass-Flow Rate (MFR) (230°C/2.16					
kg)	30 to 45	g/10 min	ASTM D1238		
Ash Content	0.025 to 0.050	%			
Thermal Creep Temperature ¹	64 to 90	°C			
Thermal-oxidative Deterioration (150°C)	15.0	day			
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (R-Scale)	40 to 88				
Mechanical	Nominal Value	Unit	Test Method		
Flexural Modulus	1100	MPa	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact (23°C)	90	J/m	ASTM D256		
Thermal	Nominal Value	Unit			

Vicat Softening Temperature ²	126 to 150	°C	
NOTE			
1.	at load 0.46 H/mm²		
2	in liquid medium under	force 10 H	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

