

HIFOR® LT74113

Linear Low Density Polyethylene

Westlake Chemical Corporation

Message:

WESTLAKE HIFOR Polyethylene LT74113 is a high strength hexene linear low density polyethylene containing no slip and medium antiblock. It is designed for blown applications and is well suited for consumer and industrial packaging markets which require impact and tear strength. Films produced using LT74113 exhibit low imperfections and facilitate production at thinner gauges

General Information			
Additive	Medium Antiblock		
Features	Good Impact Resistance		
	Good Tear Strength		
	High Strength		
	Medium Antiblocking		
Uses	Film		
	Food Packaging		
	Packaging		
Agency Ratings	FDA 21 CFR 177.1520		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.920	g/cm ³	ASTM D4883
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.0	g/10 min	ASTM D1238
Films	Nominal Value	Unit	Test Method
Secant Modulus			ASTM D882
1% Secant, MD	221	MPa	
1% Secant, TD	241	MPa	
Tensile Strength			ASTM D882
MD : Break	50.0	MPa	
TD : Break	39.0	MPa	
Tensile Elongation			ASTM D882
MD : Break	750	%	
TD : Break	1000	%	
Dart Drop Impact	170	g	ASTM D1709
Optical	Nominal Value	Unit	Test Method
Gloss (45°)	45		ASTM D2457
Haze	14	%	ASTM D1003

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any

infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

