Trademark PE LD0720F

Low Density Polyethylene

Trademark Plastics Corporation

Message:

Trademark PE LD0720F is a Low Density Polyethylene product. It is available in North America. Applications of Trademark PE LD0720F include bags/liners, film, food contact applications and wrap. Characteristics include: Antiblock Food Contact Acceptable Good Processability Good Toughness Slip

General Information				
Additive	Medium Antiblock			
	Medium Slip			
Features	Additive Free			
	Food Contact Acceptable			
	Good Drawdown			
	Good Processability			
	Good Toughness			
	Medium Antiblocking			
	Medium Slip			
Uses	Film			
	Heavy-duty Bags			
	Liners			
	Shrink Wrap			
Agency Ratings	FDA 21 CFR 177.1520(c) 2.1			
Physical	Nominal Value	Unit	Test Method	
Density	0.920	g/cm³	ASTM D1505	
Melt Mass-Flow Rate (MFR) (190°C/2.16				
kg)	0.70	g/10 min	ASTM D1238	
Films	Nominal Value	Unit	Test Method	
Film Thickness - Tested	51	μm		
Secant Modulus			ASTM D882	
1% Secant, MD : 51 μm , Blown Film	172	MPa		
1% Secant, TD : 51 µm, Blown Film	217	MPa		
Tensile Strength			ASTM D882	
MD : Break, 51 µm,Blown Film	23.4	MPa		
TD : Break, 51 µm,Blown Film	16.5	MPa		

Tensile Elongation			ASTM D882
MD : Break, 51 µm,Blown Film	170	%	
TD : Break, 51 µm,Blown Film	490	%	
Dart Drop Impact (51 µm, Blown Film)	130	g	ASTM D1709
Elmendorf Tear Strength			ASTM D1922
MD : 51 µm, Blown Film	290	g	
TD : 51 µm, Blown Film	180	g	
Optical	Nominal Value	Unit	Test Method
Haze (50.8 µm, Blown Film)	11	%	ASTM D1003
Extrusion	Nominal Value	Unit	
Melt Temperature	182 to 199	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

