SILPURAN® 8020/40

Silicone

Wacker Chemie AG

Message:

Cured Properties

Silicone Rubber, HTV
Gaskets, Plastics and Rubber Processing
Membranes, Pharmaceuticals & Healthcare
Balloons, Pharmaceuticals & Healthcare
Seals (HealthCare / Pharma), Pharmaceuticals & Healthcare
Valves (HealthCare / Pharma), Pharmaceuticals & Healthcare

General Information									
Features	Biocompatible								
	BPA Free Breathable Good Chemical Resistance								
	Good Flexibility								
	Good Sterilizability Good Thermal Stability								
						High Gas Permeability			
	High Heat Resistance High Purity Low to No Odor								
							Low to No Water Absorptio	n	
							Non-Toxic		
		Steam Resistant							
Uses	Body Implants								
	Medical Devices								
	Medical/Healthcare Applications								
	Pharmaceuticals								
Agency Ratings	ISO 10993								
	USP Class VI								
Processing Method	Compression Molding								
	Press Molding								
Uncured Properties	Nominal Value	Unit	Test Method						
Color	Clear/Transparent								
Density	1.12	g/cm³	DIN 53479						

Nominal Value

Unit

Test Method

Shore Hardness (Shore A)	40		DIN 53505
Tensile Strength	11.5	MPa	DIN 53504
Tensile Elongation at Break	830	%	DIN 53504
Compression Set	25	%	DIN ISO 815-B
Tear Strength	38.0	kN/m	ASTM D624B
Rebound Resilience	55	%	DIN 53512

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

