

# DuraMax™ DMX 8060NC

Thermoplastic Elastomer

Advanced Polymer Alloys

## Message:

DuraMax™DMX 8060NC is a thermoplastic elastomer (TPE) material. This product is available in North America, Europe or Asia Pacific.

General Information			
Appearance	Natural color		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.17	g/cm <sup>3</sup>	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shaw A	59		ASTM D2240
Shaw A, 15 seconds	51		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Set	9	%	ASTM D412
Tensile Stress (100% Strain)	2.76	MPa	ASTM D412
Tensile Strength (Break)	10.3	MPa	ASTM D412
Tensile Elongation (Break)	420	%	ASTM D412
Compression Set (70°C, 22 hr)	64	%	ASTM D395B
Additional Information			

Tear, Graves Die C: 160 psi

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

