

TAISOX 8012

High Density Polyethylene
Formosa Plastics Corporation

Message:

TAISOX 8012 is a high density polyethylene material. This product is available in North America, Europe or Asia Pacific. The processing method is extrusion.

The main features of TAISOX 8012 are:

- Good processability
- Impact resistance

Typical application areas include:

- bag/lining
- sheet
- Sling/Rope
- Foam
- Yarn

General Information			
Features	High density Gloss, Medium Impact resistance, high Workability, good Good stretchability		
Uses	Bags Monochrome high toughness line Foam Sheet Rope Web		
Forms	Particle		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.957	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.1	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	69		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Yield	29.4	MPa	ASTM D638
Fracture	37.3	MPa	ASTM D638
Tensile Elongation (Break)	1000	%	ASTM D638
Impact	Nominal Value	Unit	Test Method

Tensile Impact Strength	343	kJ/m ²	ASTM D1822
Thermal	Nominal Value	Unit	
Melting Temperature	134	°C	
Additional Information			

Notched Izod Impact Strength, ASTM D256: 50 kg-cm/cm²Injection Melt Temperature Yarn: 190 to 210°CInjection Melt Temperature Monofilament: 260 to 280°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

