

Orevac® 9309

Ethylene Vinyl Acetate Copolymer

Arkema

Message:

Orevac® 9309 is an Ethylene Vinyl Acetate Copolymer (EVA) product. It can be processed by cast film and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Applications of Orevac® 9309 include film and hose/tubing.

| General Information | | | |
|-----------------------------|---------------|----------|-------------|
| Features | Terpolymer | | |
| Uses | Cast Film | | |
| | Hose | | |
| Forms | Pellets | | |
| Processing Method | Cast Film | | |
| Physical | Nominal Value | Unit | Test Method |
| Melt Mass-Flow Rate (MFR) | 4.0 | g/10 min | ASTM D1238 |
| Hardness | Nominal Value | Unit | Test Method |
| Shore Hardness (Shore D) | 70 | | ISO 868 |
| Thermal | Nominal Value | Unit | Test Method |
| Vicat Softening Temperature | 77.0 | °C | ASTM D1525 |
| Melting Temperature | 100 | °C | DSC |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

