

Stat-Tech™ ATC-000/000 AS BLACK

Acetal (POM) Copolymer

PolyOne Corporation

Message:

Stat-Tech™ ATC-000/000 AS BLACK is an Acetal (POM) Copolymer product. It can be processed by injection molding and is available in Europe.

Characteristics include:

RoHS Compliant

Wear Resistant

General Information			
Features	Antistatic		
	Good Abrasion Resistance		
RoHS Compliance	RoHS Compliant		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	1.39	g/cm³	ISO 1183
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus (23°C)	2500	MPa	ISO 527
Tensile Strength (Break, 23°C)	55.0	MPa	ISO 527
Tensile Elongation (Break, 23°C)	18	%	ISO 527
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C, Injection Molded)	6.0	kJ/m²	ISO 179/1eA
Charpy Unnotched Impact Strength (23°C, Injection Molded)	85	kJ/m²	ISO 179/1eU
Electrical	Nominal Value	Unit	Test Method
Surface Resistivity	1.0E+11	ohms	IEC 60093

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT