

Ablebond 77-1S

Epoxy; Epoxide
Henkel Ablestik

Message:

Ablebond 77-1S is an Epoxy; Epoxide (Epoxy) material. It is available in North America. Primary attribute of Ablebond 77-1S: Insulating.
Typical application of Ablebond 77-1S: Adhesives/Tapes

| General Information | | | |
|---------------------|-------------------------|---------|-------------|
| Features | Electrically Insulating | | |
| Uses | Adhesives | | |
| Forms | Paste | | |
| Electrical | Nominal Value | Unit | Test Method |
| Volume Resistivity | 1.3E+12 | ohms·cm | ASTM D257 |
| Thermoset | Nominal Value | Unit | |
| Pot Life (23°C) | 120000 | min | |
| Shelf Life (5°C) | 26 | wk | |
| Demold Time (150°C) | 3.0 | min | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT