

# Yanshan PE LD157

Low Density Polyethylene  
SINOPEC Beijing Yanshan Petrochemical

Message:

Yanshan PE LD157 is a Low Density Polyethylene product. It can be processed by blow molding or film extrusion and is available in Asia Pacific. Applications of Yanshan PE LD157 include film, wire & cable and wrap. Primary characteristic: crosslinkable.

General Information	
Features	Crosslinkable
Uses	Cable Jacketing
	Film
	Multilayer Film
	Shrink Wrap
Processing Method	Blow Molding
	Film Extrusion

Physical	Nominal Value	Unit	Test Method
Density	0.931	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR)	0.60	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	10.0	MPa	ASTM D638
Tensile Elongation (Break)	100	%	ASTM D638

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

  
WECHAT