

LTP ZE-2601 Al₂O₃/GF 30%

Thermoplastic

Chengdu Letian Plastics Co., Ltd

Message:

precise molding materials -LTPZE- 2600 serials LTPZE- 2600 serials reinforced by nano-Al₂O₃ made a breakthrough on 0.2mm ultra-thin molding. The molding product is smooth and brightness with the surface flexing low than 1% , and can meet the dimension precision requirement of parts and shells for high level electric appliances.

| General Information | | |
|--------------------------------|----------------------------------------------------------|-------------------|
| Filler / Reinforcement | Glass\Inorganic,30% Filler by Weight Unspecified Nano | |
| Features | Good Surface Finish | |
| Uses | Appliances Electrical/Electronic Applications | |
| Physical | Nominal Value | Unit |
| Density | 1.65 | g/cm ³ |
| Melt Mass-Flow Rate (MFR) | 120 to 150 | g/10 min |
| Flow Length | 8.00 | mm |
| Flexural Deformation | 1.00 | mm |
| Mechanical | Nominal Value | Unit |
| Tensile Stress | 180 | MPa |
| Tensile Strain (Break) | 1.2 | % |
| Impact | Nominal Value | Unit |
| Charpy Notched Impact Strength | 12 | kJ/m ² |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT