

Shandong PA66 A2LG6301

Polyamide 66

Shandong Dongchen Engineering Plastics Co., Ltd.

Message:

Shandong PA66 A2LG6301 is a Polyamide 66 (Nylon 66) material filled with filler. It is available in Asia Pacific.

Important attributes of Shandong PA66 A2LG6301 are:

Flame Retardant

Heat Resistant

High Strength

Wear Resistant

Typical applications include:

Appliances

Automotive

Electrical/Electronic Applications

General Information	
Filler / Reinforcement	Filler
Additive	Flame Retardant
Features	Flame Retardant
	Good Wear Resistance
	High Heat Resistance
	High Strength
Uses	Appliance Components
	Automotive Applications
	Electrical/Electronic Applications

Physical	Nominal Value	Unit
Ash Content	30	%
Mechanical	Nominal Value	Unit
Tensile Stress (Yield)	165	MPa
Tensile Strain (Break)	2.0	%
Flexural Modulus	8500	MPa
Flexural Stress	200	MPa
Impact	Nominal Value	Unit
Charpy Notched Impact Strength	8.0	kJ/m ²
Charpy Unnotched Impact Strength	65	kJ/m ²

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

