

Sylvin 86043-66 Clear

Polyvinyl Chloride
Sylvin Technologies Incorporated

Message:

Sylvin 86043-66 Clear Is A Vinyl Compound Formulated With A Citrate Plasticizer For Extrusion Applications That Require Prop 65 And REACH Compliance.

General Information			
Additive	Plasticizer		
Features	Non-phthalic acid ester-citrate		
	General		
Uses	Industrial application		
	General		
Agency Ratings	EC 1907/2006 (REACH)		
	OEHHA Proposition 65		
Appearance	Clear/transparent		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.23	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shaw A	66		ASTM D2240
Shaw A, 10 seconds	66		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	13.8	MPa	ASTM D638
Tensile Elongation (Break)	430	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	48.2	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	157 - 168	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

