

# Topolymer® 9210-751

Thermoplastic Vulcanizate

Dongguan Top Polymer Enterprise

## Message:

Topolymer® 9000s materials are extremely suitable for automotive sealing systems. Besides the above generally grades, other Topolymer® grades series exist, each with a specialty set of properties designed to fit a variety of application requirements. In addition to standard Topolymer® series, special Topolymer® grades exist or can be developed to meet unique customer requirements.

### Application:

Light colour, easy coloring. Recommended for applications requiring excellent flex fatigue resistance, excellent ozone resistance. Used in interior, encapsulation applications and sealing applications. These grades of Topolymer TPVs can be processed on conventional thermoplastics equipment for injection molding, extrusion or blow-molding.

General Information	
Features	Good Colorability
	Ozone Resistant
Uses	Automotive Applications
	Seals
Agency Ratings	EC 1907/2006 (REACH)
	FDA 21 CFR 177.2600
RoHS Compliance	RoHS Compliant
Processing Method	Blow Molding
	Encapsulating
	Extrusion
	Injection Molding

Physical	Nominal Value	Unit
Specific Gravity	0.960	g/cm³
Hardness	Nominal Value	Unit
Durometer Hardness (Shore A)	75	
Elastomers	Nominal Value	Unit
Tensile Strength	8.30	MPa
Tensile Elongation (Break)	470	%
Tear Strength	33.2	kN/m
Compression Set (70°C, 22 hr)	32	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

