

Eltex® P KS414

Polypropylene Random Copolymer
INEOS Olefins & Polymers Europe

Message:

Benefits & Features
Eltex® P KS414 is a random copolymer with a high ethylene content, developed for use primarily as the sealing layer in "coextruded bioriented film". It contains slip and anti-blocking agents.

Applications
Random copolymer specially developed for the sealing layers of "coextruded bioriented film"

General Information			
Additive	Antiblock		
	Slip		
Features	Antiblocking		
	Random Copolymer		
	Slip		
Uses	Bi-axially Oriented Film		
	Film		
RoHS Compliance	Contact Manufacturer		
Forms	Pellets		
Processing Method	Coextrusion		
	Film Extrusion		
Physical	Nominal Value	Unit	Test Method
Density (23°C)	0.895	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	7.3	g/10 min	ISO 1133
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore D, 23°C)	62		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	21.0	MPa	ISO 527-2
Flexural Modulus (23°C)	750	MPa	ISO 178
Films	Nominal Value	Unit	Test Method
Heat Seal Threshold ¹	115	°C	Internal Method
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (0.45 MPa, Unannealed)	60.0	°C	ISO 75-2/B
Vicat Softening Temperature	120	°C	ISO 306/A50
Peak Melting Temperature	134	°C	ASTM D3417

NOTE

1. 1s, 3 bars, 100 mm/min, 100 g/cm

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

