PIVINEL[™] BC-33

Polyvinyl Chloride

HELLENIC CABLES S.A.

Message:

Description: PVC based compound with big hardness suitable for the production of electrical pipes (channels) Packaging: In big bags of approximately 700kg Use: Hard spiral for electrical pipes for the protection of cables, channels

General Information			
Features	High Hardness		
Uses	Electrical/Electronic Applications		
	Piping		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	
Specific Gravity	1.47	g/cm ³	
Extrusion	Nominal Value	Unit	
Cylinder Zone 1 Temp.	140	°C	
Cylinder Zone 2 Temp.	145	°C	
Cylinder Zone 3 Temp.	155	°C	
Cylinder Zone 4 Temp.	155	°C	
Cylinder Zone 5 Temp.	155	°C	
Cylinder Zone 6 Temp.	155	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

°C

°C

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

155

155

Tel: +86 21 5895 8519

Phone: +86 13424755533

Cylinder Zone 7 Temp.

Head Temperature

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

