# NuSil MED-4070

### Rubber

## NuSil Technology

#### Message:

NuSil Technology's restricted materials may be considered for use in short-term implant applications, 29 days or less, or for external applications. High consistency rubber, or HCR, consists of high molecular weight polymer combined with silica to produce a material that can be molded, extruded, or calendared into a useful end product. An HCR has the consistency of clay and is primarily formulated in a one or two part system (peroxide and platinum catalysts respectively).

Most platinum cure high consistency rubbers are two component systems with an easy-to-work-with 1:1 mix ratio. Comments: ABRASION/FATIGUE RESISTANT

General Information			
Filler / Reinforcement	Silica gel filler		
Features	High molecular weight		
	Good wear resistance		
	Fatigue resistance		
	Low shrinkage		
Uses	Medical/nursing supplies		
Agency Ratings	USP Class VI		
Processing Method	Extrusion		
	Calendering		
	Injection molding		
Mechanical	Nominal Value	Unit	
Tensile Strength (100% Strain)	4.14	MPa	
Thermoset	Nominal Value	Unit	
Thermoset Components			
Component a	Mixing ratio by weight: 1.0		
Component B	Mixing ratio by weight: 1.0		
Post Cure Time (177°C)	4.0	hr	
Additional Information	Nominal Value	Unit	
Cure System	Platinum		
Plasticity: 120 mils			
Uncured Properties	Nominal Value	Unit	
Density	1.19	g/cm³	
Curing Time (138°C)	0.17	hr	
Pot Life (25°C)	120	min	
Cured Properties	Nominal Value	Unit	
Shore Hardness (Shore A)	70		
Tensile Strength	9.14	MPa	
Tensile Elongation at Break	700	%	

Tear Strength	49.9	kN/m
---------------	------	------

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

