

# Hyundai EP XLPE XP670/Natural

Crosslinked Polyethylene

HYUNDAI EP Co., Ltd.

## Message:

Hyundai EP XLPE XP670/Natural is a Crosslinked Polyethylene product. It is available in Asia Pacific. Typical application: Plumbing/Piping/Potable Water.

Characteristics include:

Crosslinkable

Heat Resistant

High ESCR (Stress Crack Resistant)

General Information			
Features	Crosslinkable		
	General Purpose		
	High ESCR (Stress Crack Resist.)		
	High Heat Resistance		
Uses	Piping		
	Plumbing Parts		
Appearance	Natural Color		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.952	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/5.0 kg)	1.1	g/10 min	ASTM D1238
Degree of Crosslinking	70	%	DIN 16892
Moisture Content	0.20	%	Internal Method
Black Spot <sup>1</sup>	0.00	count/g	Internal Method
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	26.5	MPa	ASTM D638
Tensile Elongation (Break)	500	%	ASTM D638
NOTE			
1.	2.5 grams		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

