## Wanthane® WHT-1690AB

Thermoplastic Polyurethane Elastomer (Polyester)

Wanhua Chemical Group Co., Ltd.

## Message:

WHT-1690AB is polyester-based TPU for extrusion molding applications, including blow molding and T-die extrusion, supplied in form of transparent, translucent, colorless or slightly yellowish film with excellent strength and tear resistance.

Package, Exterior Decoration Parts, Fabric Coating.

General Information					
Features	Good strength				
	Good tear strength				
Uses	Packaging				
	Coating application				
	Fabric				
	Decorative parts				
Appearance	Translucent				
	Transparent-Slightly Yellow				
	Colorless				
Forms	Films				
Processing Method	Extrusion				
Physical	Nominal Value	Unit	Test Method		
Density	1.21	g/cm³	ASTM D792		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A)	90		ASTM D2240		
Elastomers	Nominal Value	Unit	Test Method		
Tensile Stress			ASTM D412		
100% strain	10.0	MPa	ASTM D412		
300% strain	18.0	МРа	ASTM D412		
Tensile Strength	36.0	MPa	ASTM D412		
Tensile Elongation (Break)	490	%	ASTM D412		
Tear Strength	120	kN/m	ASTM D624		
Thermal	Nominal Value	Unit	Test Method		
Glass Transition Temperature	-20.0	°C	ASTM D3417		
Optical	Nominal Value	Unit	Test Method		
Transmittance	89.0	%	ASTM D1003		
Extrusion	Nominal Value	Unit			
Drying Temperature	80.0 - 110	°C			

Drying Time	2.0 - 3.0	hr	
Cylinder Zone 1 Temp.	180	°C	
Cylinder Zone 2 Temp.	185	°C	
Cylinder Zone 3 Temp.	190	°C	
Cylinder Zone 4 Temp.	195	°C	
Cylinder Zone 5 Temp.	195 - 200	°C	
Extrusion instructions			

Extruder Feed Section: 175

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

