

Durez® 29781

Phenolic

Sumitomo Bakelite North America, Inc.

Message:

Durez 29781 is a finely pulverized two-step phenolic resin.

Durez 29781 is recommended for use in the manufacture of dry mix truck blocks and disc brake pads.

Durez 29781 contributes good friction and fade resistance to formulations.

General Information			
Features	Good Color Stability		
Uses	Automotive Applications		
Thermal	Nominal Value	Unit	Test Method
Softening Point ¹	80	°C	Internal Method
Hexa	8.5	%	Internal Method
Inclined Plate Flow (125°C)	4.00	cm	Internal Method
Screen Mesh ²	< 1.0	%	Internal Method
Thermoset	Nominal Value	Unit	Test Method
Post Cure Time (165°C)	8.3E-3	hr	
NOTE			
1.	cap. shrink		
2.	200 Mesh		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

