

Fainplast PVC PH 45/N

Flexible Polyvinyl Chloride

Fainplast Compounds S.r.l

Message:

Fainplast PVC PH 45/N is a Flexible Polyvinyl Chloride product. It can be processed by extrusion or profile extrusion and is available in Africa & Middle East, Europe, Latin America, or North America.

| General Information | |
|---------------------|--------------------------------|
| Uses | Profiles |
| Appearance | Clear/Transparent |
| Processing Method | Extrusion Profile Extrusion |

| Physical | Nominal Value | Unit | Test Method |
|--------------------------|---------------|-------------------|-------------|
| Density | 1.15 | g/cm ³ | ISO 1183 |
| Hardness | Nominal Value | Unit | Test Method |
| Shore Hardness (Shore A) | 45 | | ISO 868 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Stress (Break) | > 8.00 | MPa | ISO 527-2 |
| Tensile Strain (Break) | > 450 | % | ISO 527-2 |
| Thermal | Nominal Value | Unit | Test Method |
| Cold Flexibility | -53 | °C | ISO 458/2 |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT