

Shandong PP KPP30-2

Polypropylene

Shandong Dongchen Engineering Plastics Co., Ltd.

Message:

Shandong PP KPP30-2 is a Polypropylene material filled with mineral. It is available in Asia Pacific.

Important attributes of Shandong PP KPP30-2 are:

Good Toughness

Rigid

Typical applications include:

Appliances

Automotive

Electrical/Electronic Applications

Housings

General Information	
Filler / Reinforcement	Mineral
Features	Good Toughness
	High Rigidity
Uses	Appliance Components
	Automotive Applications
	Battery Cases
	Electrical/Electronic Applications

Mechanical	Nominal Value	Unit
Tensile Stress (Yield)	> 25.0	MPa
Flexural Stress	> 30.0	MPa
Impact	Nominal Value	Unit
Notched Izod Impact Strength	> 10	kJ/m ²
Unnotched Izod Impact Strength	> 70	kJ/m ²
Thermal	Nominal Value	Unit
Heat Deflection Temperature (0.45 MPa, Unannealed)	> 100	°C
Additional Information	Nominal Value	Unit
Residue of Combustion	28 to 32	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

