# YUPLENE® BH3800

## Polypropylene Impact Copolymer

#### SK Global Chemical

#### Message:

YUPLENE BH3800 is an ultra high impact propylene copolymer designed for injection molding and compounding applications. YUPLENE BH3800 has excellent properties in impact strength as well as stiffness, flow, mechanical properties and heat resistance, which make YUPLENE BH3800 suitable for auto parts, electric appliances, large size containers, thin wall and very high speed injection applications.

General Information				
Features	Good Flow			
	Good Stiffness			
	High Heat Resistance			
	Impact Copolymer			
	Ultra High Impact Resistance			
Uses	Appliances			
	Automotive Applications			
	Compounding			
	Containers			
	Electrical/Electronic Applications			
	Industrial Applications			
	Thin-walled Parts			
Processing Method	Compounding			
	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Melt Mass-Flow Rate (MFR) (230°C/2.16	20	<b>40</b>	ACTN 4 D4000	
kg)	28	g/10 min	ASTM D1238	
Spiral Flow	> 80.0	cm	Internal Method	

Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16			
kg)	28	g/10 min	ASTM D1238
Spiral Flow	> 80.0	cm	Internal Method
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	82		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	22.6	MPa	ASTM D638
Tensile Elongation (Break)	< 300	%	ASTM D638
Flexural Modulus	1180	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
-20°C	69	J/m	
23°C	170	J/m	
Aging	Nominal Value	Unit	Test Method

Accelerated Oven Aging - in Air (150°C)	15.0	day	ASTM D3012
Heat Deflection Temperature	110	°C	ASTM D648
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	150	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

### Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

