SQUARE® LSG6931-20A/B

Silicone Rubber, LSR

Shenzhen SQUARE Silicone Co., Ltd.

Message:

Electronic encapsulation and heat-eliminating silicone gel

Product description

This product is one kind of 2-part liquid silicone rubber, catalyzed by platinum, mixing ratio of parts A:B=1:1; mainly suitable for euthermic electric parts PCB,CPU, MPU and LED heat-eliminating and encapsulation, with the features of high temperature-resistant and outstanding heat-eliminating.

Key Features

Oiltight, the fluidity and heat conduction property can be adjusted with requirement, non-toxic and eco-friendly.

Application

Suitable for electric parts encapsulation and heat-eliminating.

General Information				
Features	Environmental protection			
	Heat resistance, high			
	Non-toxic			
Uses	Encapsulant			
	Electrical/Electronic Applications			
Appearance	White			
Processing Method	Enclosure			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.35	g/cm³	ASTM D792	
Thermal	Nominal Value	Unit		
Thermal Conductivity	1.6	W/m/K		
Thermoset	Nominal Value	Unit		
Thermoset Components				
Component a	Mixing ratio by weight: 1.0	Mixing ratio by weight: 1.0		
Component B	Mixing ratio by weight: 1.0	Mixing ratio by weight: 1.0		
Shelf Life	52	wk		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

