

MOSTEN NB 108

Polypropylene Homopolymer

UNIPETROL RPA

Message:

Polypropylene Mosten NB 108 is a homopolymer with moderate molecular weight distribution, intended for fibre applications. It's addition system offers good anti-gas fading properties. It is also suitable for compounding.

General Information			
Additive	Anti-gas fading		
Features	Food Contact Acceptable		
	Gas-fading Resistant		
	Homopolymer		
	Medium Molecular Weight		
Uses	Compounding		
	Fibers		
Agency Ratings	EC 1935/2004		
	EU No 10/2011		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	8.0	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	35.0	MPa	ISO 527-2
Tensile Strain (Break)	> 100	%	ISO 527-2
Flexural Modulus	1700	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C)	3.0	kJ/m ²	ISO 179
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (1.8 MPa, Unannealed)	56.0	°C	ISO 75-2/A
Vicat Softening Temperature	154	°C	ISO 306

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co., Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

