

RR Advantage PPB 20 NO BREAK

Polypropylene Impact Copolymer

Resin Resource, Inc.

Message:

RR Advantage PPB 20 NO BREAK is a Polypropylene Impact Copolymer (PP Impact Copolymer) material. It is available in North America for injection molding. Primary attribute of RR Advantage PPB 20 NO BREAK: Copolymer.

General Information			
Features	Impact Copolymer		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR)	20	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	19.7	MPa	ASTM D638
Tensile Elongation (Yield)	5.5	%	ASTM D638
Flexural Modulus	1000	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	No Break		ASTM D256
Thermal	Nominal Value	Unit	
Melting Temperature	162	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

