Edgetek™ AS/018 White

Acrylonitrile Butadiene Styrene

PolyOne Corporation

Message:

The Edgetek® Engineering Thermoplastic Compounds portfolio covers a broad range of standard and custom-formulated high performance materials. This portfolio includes high-temperature materials for elevated service temperature environments, high-modulus / structural materials for load-bearing and high-strength applications and flame-retardant products. These compounds are based on select engineering thermoplastic resins that are compounded with reinforcing additives such as carbon fiber, glass fiber and glass beads.

General Information			
Features	Amorphous		
	Good Moldability		
	Good Toughness		
Uses	Appliances		
	Automotive Applications		
	Consumer Applications		
	General Purpose		
	Industrial Applications		
	Structural Parts		
RoHS Compliance	RoHS Compliant		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.21	g/cm³	ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Yield)	40.0	MPa	ASTM D638
Tensile Elongation ² (Break)	2.0 to 3.0	%	ASTM D638
Flexural Modulus ³	2690	MPa	ASTM D790
Flexural Strength ⁴	68.9	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	160	J/m	ASTM D256
NOTE			
1.	51 mm/min		
2.	Туре І		
3.	13 mm/min		
4.	13 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

