

Maxelast® F02-074B-8

Thermoplastic Elastomer

Nantong Polymax Elastomer Technology, Co., Ltd

Message:

Maxelast® F02-074B-8 is a Thermoplastic Elastomer (TPE) material. It is available in Asia Pacific, Europe, or North America for extrusion.

Important attributes of Maxelast® F02-074B-8 are:

Flame Retardant

Halogen Free

Typical application of Maxelast® F02-074B-8: Wire & Cable

General Information			
Additive	Flame Retardant		
Features	Flame Retardant		
	Halogen Free		
Agency Ratings	IEC 60332-1		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.16	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	85		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress			ASTM D412
100% Strain	7.60	MPa	
300% Strain	8.66	MPa	
Tensile Strength (Yield)	11.2	MPa	ASTM D412
Tensile Elongation (Break)	580	%	ASTM D412

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT